

Flat Washer Size Chart (US Standard)

Tip: Set your PDF viewer to "Actual size" before printing to maintain scale.

Bolt Size	Inside Diameter (ID)	Outside Diameter (OD)	Thickness
#6	0.156" (3.96mm)	0.375" (9.53mm)	0.049" (1.24mm)
#8	0.188" (4.78mm)	0.438" (11.11mm)	0.049" (1.24mm)
#10	0.219" (5.56mm)	0.500" (12.70mm)	0.049" (1.24mm)
1/4"	0.281" (7.14mm)	0.625" (15.88mm)	0.065" (1.65mm)
5/16"	0.344" (8.74mm)	0.688" (17.48mm)	0.065" (1.65mm)
3/8"	0.406" (10.31mm)	0.812" (20.62mm)	0.065" (1.65mm)
7/16"	0.469" (11.91mm)	0.922" (23.42mm)	0.065" (1.65mm)
1/2"	0.531" (13.49mm)	1.062" (26.97mm)	0.095" (2.41mm)
5/8"	0.656" (16.66mm)	1.312" (33.32mm)	0.095" (2.41mm)
3/4"	0.812" (20.62mm)	1.469" (37.31mm)	0.134" (3.40mm)

- **SAE Standard:** Standard pattern flat washers shown above
- **USS Wide Pattern:** Larger OD washers also available for increased bearing surface
- **Always use under nuts** to prevent surface damage and distribute load
- **Fender Washers:** Available with 3-4× larger OD for soft materials

Quality Products That Last - Right Off the Rack®

www.albanycountyfasteners.com

© 2025 Albany County Fasteners. All rights reserved.