

Stainless Steel Closed End Blind Rivets Specifications



Diameter	Rivet Number	Grip Range	Rivet Length	Head Diameter	Head Height	Mandrel Diameter	Hole Size (Drill #)	Shear Strength	Tensile Strength
1/8"	4-2	.063 - .125	.360	.250	.040	.076	.129 - .133 (#30)	400	450
	4-3	.126 - .187	.422						
	4-4	.188 - .250	.485						
	4-5	.251 - .312	.547						
	4-6	.313 - .375	.610						
	4-8	.376 - .500	.735						
5/32"	5-2	.020 - .125	.375	.312	.050	.095	.160 - .164 (#20)	700	800
	5-3	.126 - .187	.437						
	5-4	.188 - .250	.500						
	5-6	.251 - .375	.625						
	5-8	.376 - .500	.750						
	5-10	.501 - .625	.875						
3/16"	6-2	.020 - .125	.406	.375	.060	.114	.192 - .196 (#11)	850	900
	6-3	.126 - .187	.468						
	6-4	.188 - .250	.531						
	6-6	.251 - .375	.656						
	6-8	.376 - .500	.781						
	6-10	.501 - .625	.906						
	6-12	.626 - .750	1.026						
1/4"	8-2	.020 - .125	.445	.500	.080	.151	.257 - .261 (F)	1520	1955
	8-4	.125 - .250	.570						
	8-6	.251 - .375	.695						
	8-8	.376 - .500	.820						
	8-10	.501 - .625	.945						
	8-12	.626 - .750	1.070						
	8-14	.751 - .875	1.195						
	8-16	.876 - 1.00	1.320						